

# Galatea TG

Interior and exterior spotlight with galvanised brass face, tempered glass, aluminium heatsink anodised, directional reflector/lens. Nichia LED chip with CRI value >90



| Code            | LED Colour | Lens |
|-----------------|------------|------|
| 5250CLED2700.9  | 2700K      | 44°  |
| 5250CLED2700.9M | 2700K      | 29°  |
| 5250CLED2700.9N | 2700K      | 14°  |
| 5250CLED3200.9  | 3200K      | 44°  |
| 5250CLED3200.9M | 3200K      | 29°  |
| 5250CLED3200.9N | 3200K      | 14°  |
| 5250CLED4000.9  | 4000K      | 44°  |
| 5250CLED4000.9M | 4000K      | 29°  |
| 5250CLED4000.9N | 4000K      | 14°  |
| 5250CLEDR       | RED        | 44°  |

|                               |                         |
|-------------------------------|-------------------------|
| <b>Finish</b>                 | Chrome                  |
| <b>LED Colour Temperature</b> | 2700K<br>3200K<br>4000K |
| <b>LED Colour</b>             | RED                     |



Gruppo di rischio Fotobiologico EN 62471  
Photobiological risk group EN 62471  
Groupe de risque photobiologique EN 62471



## Power Led

|                |
|----------------|
| 10/30<br>VDC   |
| 5<br>W ATT     |
| DIMMER<br>6018 |

## CRI >90

Indice di resa cromatica  
color rendering index  
indice de rendu des couleurs

