



Prometeo QRP

Interior and exterior spotlight with galvanised brass body, tempered glass, aluminium heatsink anodised, directional reflector/lens.

Nichia LED chip with CRI value >90

Finish	Black
LED Colour Temperature	2700K 3200K 4000K
LED Colour	RED

Code	LED Colour	Lens
5186BLKLED2700.9	2700K	31°
5186BLKLED2700.9M	2700K	23°
5186BLKLED2700.9N	2700K	13°
5186BLKLED2700.9EL	2700K	21°-14° Elliptical
5186BLKLED3200.9	3200K	31°
5186BLKLED3200.9M	3200K	23°
5186BLKLED3200.9N	3200K	13°
5186BLKLED3200.9EL	3200K	21°-14° Elliptical
5186BLKLED4000.9	4000K	31°
5186BLKLED4000.9M	4000K	23°
5186BLKLED4000.9N	4000K	13°
5186BLKLED4000.9EL	4000K	21°-14° Elliptical
5186BLKLEDR	RED	31°



Gruppo di rischio Fotobiologico EN 62471
Photobiological risk group EN 62471
Groupe de risque photobiologique EN 62471



PowerLED

10/30 VDC
3 WATT
DIMMER 6018

CRI >90

Indice di resa cromatica
color rendering index
indice de rendu des couleurs

