

# SIDE VIEW LED NEON FLEX GEN II



**On Request** Pre-cut lengths with IP68 connectors

Can be installed in continuous 20m length if powered from both ends



Photobiological risk group EN 62471




## LED

24 VDC
12 W/m W/B/G/Y/A
7.2 W/m R/O
MAX LENGTH 20m
DIMMER
MAX 320 LUMEN/m
60 LED/m
BENDING RAD. 80mm




Compatible Drivers For 240V Use

Please contact us for more information on compatible drivers



Aluminium U-Clip 50mm  
NFS.U\_CLIP




Aluminium U-Channel 1m  
NFS.U\_CHANNEL\_1M

## SINGLE COLOUR LED 24V

NFS5050.120-11.5-24V.2700  
NFS5050.120-11.5-24V.3000  
NFS5050.120-11.5-24V.4000  
NFS5050.120-11.5-24V.6000  
NFS5050.120-11.5-24V.RED  
NFS5050.120-11.5-24V.ORA  
NFS5050.120-11.5-24V.BLUE  
NFS5050.120-11.5-24V.GRE  
NFS5050.120-11.5-24V.YEL  
NFS5050.120-11.5-24V.AMB

Warm white 2700K  
Neutral white 3000K  
Daylight white 4500K  
Cool white 6000K  
Red  
Orange  
Blue  
Green  
Yellow  
Amber




Max. length 20 metres if powered from both ends, 10 metres if powered from one end.  
Min. cutting length: white, yellow, blue, green, amber = 100mm  
Min cutting length: red, orange = 166.7mm

## Available Connectors:



DIY IP67 Connector  
Available in following specification:  
- Bottom  
- Side [left or right]  
- End [straight]



IP68 Injection Moulded Connector  
Available in following specification:  
- Bottom  
- Side [left or right]  
- End [straight]