





Constant Voltage PVC Neon Flex LED Strip - Top View

Product Images





Short Description

Neon effect LED strip light with single colour output.


- IP68 underwater rated casing with IP68 injection moulded connectors and end caps
- Underwater rated to a maximum installation depth of 1.50m
- Chlorine and Bromine safe - suitable for swimming pool installation
- Uniform neon light output
- 120° beam output
- White in choice of 2700°K, 3000°K, 4000°K, 5000°K or 6000°K
- Available in static colours such as blue, red, green, yellow, amber
- 3 year warranty

- Dimmable with Dali, DMX, PWM
- Top view light output - flex in the same direction of light
- Custom made to order in specified lengths

Description







16.5x16.5mm Top View Neon Flex PVC construction IP68 Dimmable 12Vdc available on request Constant current version also available




| Code | CCT | CRI | LM/m | Watt/M | Cut Unit | Min. Bend Radius | Max. Length | Voltage | Type |
|--------------------|------------|-----|------|--------|---------------|------------------|------------------------|---------|------|
| NFTCV.10.24V.2200 | 2000-2200 | >90 | 270 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.2400 | 2300-2500 | >90 | 275 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.2700 | 2600-2800 | >90 | 320 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.3000 | 2900-3100 | >90 | 300 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.3500 | 3400-3700 | >90 | 300 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.4000 | 3800-4300 | >90 | 350 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.5000 | 4800-5300 | >90 | 350 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.6000 | 5900-6400 | >90 | 350 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.R | RED | | 140 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.G | GREEN | | 410 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.B | BLUE | | 62 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.Y | YELLOW | | 115 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.10.24V.P | PINK | | 135 | 10 | 83.3mm | 60mm | 10m Single Power Input | 24Vdc | CV |
| NFTCV.13.24V.RGB | RGB | | 150 | 13 | 83.3mm | 60mm | 8m Single Power Input | 24Vdc | CV |
| NFTCV.15.24V.XRGBW | RGBW PIXEL | | | 15 | 100mm (7 LED) | 60mm | 8m Single Power Input | 24Vdc | CV |
| NFTCV.17.24V.RGBW | RGBW | | | 17 | 100mm | 60mm | 8m Single Power Input | 24Vdc | CV |
| NFTCV.17.24V.CCT | 2200-5700 | | | 17 | 100mm | | 8m Single Power Input | 24Vdc | CV |

Constant current version available for lengths above 10 metres powered from a single end

| Code | Description |
|---------------|--|
| NFT.IM.S1.600 | Injection moulded IP68 side connector for single colour PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.B1.600 | Injection moulded IP68 bottom connector for single colour PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.E1.600 | Injection moulded IP68 end connector for single colour PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.S2.600 | Injection moulded IP68 side connector for CCT PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.B2.600 | Injection moulded IP68 bottom connector for CCT PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.E2.600 | Injection moulded IP68 end connector for CCT PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.S3.600 | Injection moulded IP68 side connector for RGB PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.B3.600 | Injection moulded IP68 bottom connector for RGB PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.E3.600 | Injection moulded IP68 end connector for RGB PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.S4.600 | Injection moulded IP68 side connector for RGBW PVC 16.5x16.5mm top view - 600mm cable |
| NFT.IM.B4.600 | Injection moulded IP68 bottom connector for RGBW PVC 16.5x16.5mm top view - 600mm cable |

| Code | Description |
|---------------|--|
| NFT.IM.E4.600 | Injection moulded IP68 end connector for RGBW PVC 16.5x16.5mm top view - 600mm cable |
| NFT.E1A.600 | DIY IP67 end connector for single colour PVC 16.5x16.5mm top view - 600mm cable |
| NFT.E2A.600 | DIY IP67 end connector for CCT PVC 16.5x16.5mm top view - 600mm cable |
| NFT.E3A.600 | DIY IP67 end connector for RGB PVC 16.5x16.5mm top view - 600mm cable |
| NFT.EC1A | DIY IP67 end cap for PVC 16.5x16.5mm top view |
| NFT.UA1 | Aluminium 1m U mounting channel for 16.5x16.5mm PVC top view |
| NFT.UP1 | Transparent plastic 1m U mounting channel for 16.5x16.5mm PVC top view |
| NFT.UAC | Aluminium U mounting clip for 16.5x16.5mm PVC top view |
| NFT.USC | Stainless steel U mounting clip for 16.5x16.5mm PVC top view |
| NFT.UFLEX | Stainless steel flexible U mounting clip for 16.5x16.5mm PVC top view |

Use of the IP68 type injection moulded end connectors makes product IP68 rated and safe for use in swimming pool installations. Maximum installation depth is 1.5m. Custom cable lengths over 600mm available on request.



Additional Information

| | |
|----------------------------------|---------------|
| Weight (kg) | 0.530000 |
| Light Element Type | SMD LED 10W/m |
| Material | PVC |
| Lens Angle | 120° |
| Width (mm) | 16.50 |
| Height (mm) | 16.50 |
| Wattage | 10W / Metre |
| IP Rating | IP68 |
| Dimmer | Yes |
| LEDs Per Metre | 144 |
| CRI | >80 |
| Cutting Intervals (mm) | 83.30 |
| Lumens Per Watt (Lm) | 40.62 (3000K) |
| Luminous Flux (lm/M) | 371.9 (3000K) |
| Operating Temperature Range (°C) | -25° - +45°C |
| Strip LED Type | Flexible Neon |

